

LUKOIL ATF III

synthetic, red, multi-purpose, highperformance transmission fluid for gearbox and automatic transmissions and power steering systems

APPROVALS

MAN 339 Typ V-1/Z-1
MB-Approval 236.6
VOITH H55.6335.XX
ZF TE-ML 04D, 14A (ZF001760)

MEETS REQUIREMENTS

ALLISON C4
CATERPILLAR TO-2
FORD MERCON®
GM DEXRON®-IIIIG
RENK
VOLVO 97340

PRODUCT DESCRIPTION

The characteristics of **LUKOIL ATF III** are highest sheer stability, extremely high oxidation stability, effective corrosion protection, lowest possible foaming characteristics and a very high viscosity index.

APPLICATION

For automatic gear-boxes of passenger cars, buses, commercial vehicles or cross-country cars referring to the manufacturer's specifications.

LUKOIL ATF III can also be used as a power transmission fluid in torque converters, power steering, hydraulic clutches, hydraulic systems (deterging multigrade hydraulic oil ISO VG 32) and as gear oil referring to manufacturer's manuals.

TYPICAL TEST DATA

PROPERTY	Units	Test methods	LUKOIL ATF III
Density at 15 °C	kg/m ³	DIN 51575	850
Flash Point COC	°C	ISO 2592	209
Viscosity class	---	ISO VG	32
Viscosity at 40°C	mm ² /s	DIN 51562/T1	35
Viscosity at 100°C	mm ² /s	DIN 51562/T1	7.3
Viscosity index	---	DIN ISO 2909	180
Pourpoint	°C	DIN ISO 3016	<-48

The information given in the typical data does not constitute a specification but is an indication based on current production and can be affected by allowable production tolerances. The right to make modifications is reserved by OOO "LLK-International"