

LUKOIL AVANTGARDE ULTRA 20W-50

Super-High-Performance-Diesel (SHPD) multigrade motor oil

APPROVALS

MEETS REQUIREMENTS

ACEA E7
 API CI-4/SL
 MB 228.3

PRODUCT DESCRIPTION

LUKOIL AVANTGARDE ULTRA 20W-50 is Super-High-Performance-Diesel (SHPD) multigrade motor oil for mixed vehicle fleet, operating under extreme conditions. Also suitable for passenger car petrol and diesel engines without particle filter.

LUKOIL AVANTGARDE ULTRA 20W-50 high alkali reserve provide longtime corrosion protection and extended oil change intervals.

LUKOIL AVANTGARDE ULTRA 20W-50 prevents bore polishing, piston deposits and enhanced engine life.

APPLICATION

LUKOIL AVANTGARDE ULTRA 20W-50 is a motor oil for high performance diesel and gasoline engines including turbo-charged engines, especially for long oil change intervals.

TYPICAL TEST DATA

PROPERTY	Units	Test method	LUKOIL AVANTGARDE ULTRA 20W-50
Density at 15°C	kg/m ³	ASTM D 7042	889
Flash Point, COC	°C	ASTM D 92 SR EN ISO 2592	228
Viscosity class	--	SAE J300	20W-50
Viscosity at 100°C	mm ² s ⁻¹	ASTM D 7042 STAS 1666	18.1
Viscosity at 40°C	mm ² s ⁻¹	ASTM D 7042 STAS 1666	171
Viscosity index	--	ASTM D 7042 SR ISO 2909	117
Pour point	°C	ASTM D 97 SR 13552	<-27

The information given in the typical data does not constitute a specification but is an indication based on current production and can be affected by allowable production tolerances. The right to make modifications is reserved by OOO "LLK-International"

Aug. 18, 2017*, Page 1/1

*This document supersedes all previous versions