



# BRAKE FLUID DOT 4

Premium Synthetic DOT 4 Brake fluid

## TECHNICAL DATA SHEET

### Product Description

Veedol Brake fluid is a heavy duty brake and clutch fluid for systems requiring FMVSS 116 DOT 4 to ensure safe braking in the most severe conditions.

### Performance Specifications

Veedol Brake fluid Plus meets stringent performance requirements of:

- US FMVSS 116 DOT 4
- SAE J1704
- ISO 4925 Class 4
- JIS K2233 Class 5

### Applications

Veedol Brake fluid Dot 4 is suitable for use in commercial and passenger vehicles.

### Features/Benefits

- Possess High boiling point that helps reduce vapor locking tendency.
- Provides excellent protection to system components against rust and corrosion

### Typical Properties

Test Parameters	ASTM Method	DOT 4
Density @ 20°C, Kg/L	D 4052	1.045
Kinematic Viscosity, @ -40°C, cSt	D 445	1500
Kinematic Viscosity, @ 100°C, cSt	D 445	2.1
Dry Boiling Point ERBP °C	D 1120	266
Wet Boiling Point WERBP °C	SAE J 1703	166

Properties mentioned above are typical only, and minor variations which do not affect the product performances, are to be expected in normal manufacturing.

فيدول إنترناشيونال د.م.س.س

**VEEDOL INTERNATIONAL DMCC**

وحدة رقم 601 | إنديغو آيكون | أرض رقم إف 3 | أبراج بحيرات الجميرا | دبي | الامارات العربية المتحدة | تليفون: +971 4 3688 416 | فاكس: +971 4 3688 418  
Unit No. 601 | Indigo Icon | Plot No. F3 | Jumeirah Lakes Towers | P.O. Box No. 117019 | Dubai | United Arab Emirates

رقم الرخصة ٣٢٠٥١ DMCC رقم السجل التجاري ٣٠٠٢ DMCC

Tel: +971 4 3688 416 | Fax: +971 4 3688 418 | Email: office@veedol.ae | www.veedol.ae