

LUKOIL LUXE 10W-40

Semi-synthetic engine oils for passenger cars

APPROVALS

API SL

MEETS REQUIREMENTS

API CF

PRODUCT DESCRIPTION

LUKOIL LUXE 10W-40 is a semi-synthetic multigrade engine oil for year-round operation of passenger cars with gasoline and diesel engines.

LUKOIL LUXE 10W-40 is characterized by excellent resistance to aging and secures operation within the specified oil drain interval.

LUKOIL LUXE 10W-40 has a good viscosity-temperature behaviour and therefore good cold start properties in winter and secured lubrication in summer.

LUKOIL LUXE 10W-40 offers a very high wear and corrosion protection and enhances the service life of your engine.

APPLICATION

LUKOIL LUXE 10W-40 is intended for use as all-season oils in high performance gasoline and diesel engines of passenger cars, minibuses and light trucks where API SL/CF (or previous API categories) lubricants are recommended.

TYPICAL TEST DATA

PROPERTY	Units	Test methods	LUKOIL LUXE 10W-40
Density at 15°C	kg/m ³	ASTM D 7042	871
Flash point COC	°C	ASTM D 92 SR EN ISO 2592	>215
Viscosity class	---	SAE J 300	10W-40
Viscosity at 40°C	mm ² /s	ASTM D 7042 STAS 1666	93.5
Viscosity at 100°C	mm ² /s	ASTM D 7042 STAS 1666	13.9
Viscosity index	---	ASTM D 7042 SR ISO 2909	152
CCS -25C	mPa.s	ASTM D 5293	5924
Total base number, TBN	mgKOH/g	ASTM D 2896	7.9
Pour point	°C	ASTM D 97 SR 13552	<-35

The information given in the typical data does not constitute a specification but is an indication based on current production and can be affected by allowable production tolerances. The right to make modifications is reserved by OOO "LLK-International"