

LUKOIL LUXE 15W-40

Mineral engine oil for modern passenger cars

APPROVALS

AVTOVAZ

MEETS REQUIREMENTS

API SL/CF

PRODUCT DESCRIPTION

LUKOIL LUXE 15W-40 is a universal multigrade engine oil based on high-quality mineral base stocks and advanced additive technology.

LUKOIL LUXE 15W-40 is characterized by excellent resistance to aging and secures operation within the specified oil drain interval.

LUKOIL LUXE 15W-40 offers a very high wear and corrosion protection and enhances the service life of your engine.

APPLICATION

LUKOIL LUXE 15W-40 is an engine oil for year-round operation of passenger cars with gasoline engines, which require oils meeting API SL/CF level (or lower levels).

TYPICAL TEST DATA

PROPERTY	Units	Test methods	LUKOIL LUXE 15W-40
Density/15°C	kg/m ³	DIN 51575	882
Flash point COC	°C	ISO 2592	>220
Viscosity class	---	SAE J 300	15W-40
Viscosity/40°C	mm ² /s	DIN 51562/T1	104,5
Viscosity/100°C	mm ² /s	DIN 51562/T1	14
Viscosity index	---	DIN ISO 2909	135
CCS -20°C	mPa.s	ASTM D 5293	5671
Total base number, TBN	mgKOH/g	ASTM D 2896	7,9
Pour point	°C	DIN ISO 3016	<-35

The information given in the typical data does not constitute a specification but is an indication based on current production and can be affected by allowable production tolerances. The right to make modifications is reserved by OOO "LLK-International"