# The Professional's Choice in Motor Oil... For over a century

Revision date: 06.11.2015

# VEEDOL MAX-PRO SPECIAL LSP 10W-40

#### **Description**

**Veedol Max-Pro Special LSP 10W-40** is a Heavy Duty engine oil formulated with unique low SAPS high performance additives in combination with special selected base oils. This multigrade engine oil fulfills the latest requirements of OEM's for use in high speed four stroke diesel engines of the latest models and has the following properties:

- · Meets or exceeds the requirement of the nowadays low emission standards
- Excellent cold start properties
- Very good shear stability
- · Improved oxidation resistance
- · Very strong dispersion, therefore the deposits and sludge are restricted to a minimum
- Excellent properties against wear, corrosion and foaming

#### **Application**

This Heavy Duty engine oil is suitable for use in both on-road and off-highway applications. This engine oil contributes to low exhaust emission and particle levels which increases the lifetime of emission control systems. This product complies with and exceeds the requirements of API CJ-4. By meeting the requirements of OEM's in Europe and North America this product has a wide choice of application possibilities. This product can be applied in Euro 5 and Euro 6 engines with SCR exhaust gas system and in Euro 3 and Euro 4 engines when indicated by the manufacturer.

## Performance Specifications

API CJ-4/SM ACEA E7-12, E9-12 Meets the requirements of:
MB 228.31
MAN M 3575
Cat ECF-2/ECF-3
Cummins CES 20081
Detroit Diesel 93K218
MTU Type 2.1
Deutz DQC III-10 LA
Volvo VDS-4
Renault VI RLD-3
Global DHD-1
JASO DH-2
Mack EO-O Premium Plus

# Typicals Properties

Density at 15 °C, kg/l	0,864
Viscosity -25 °C, mPa.s	5590
Viscosity 40 °C, mm²/s	89,60
Viscosity 100 °C, mm²/s	13,90
Viscosity Index	159
Flash Point COC, °C	221
Pour Point, °C	30
Total Base Number, mgKOH/g	7,8
Sulphate Ash, %	0,92

### **Veedol International B.V.**

Kabelweg 21 | 1014 BA | Amsterdam | The Netherlands | Tel: +31(0)20-3584607 | Fax: +31(0)20-3313266

TM Registered trademark of Veedol International UK