

VEEDOL MULTIGRADE SUPER 10W-40

Description **Veedol Multigrade Super 10W-40** motor oil is based on a combination of high quality solvent refined mineral and synthetic base oils. By adding a well balanced choice of additives the following properties are obtained:

- High and stable viscosity index
- Fast cold start
- Strong resistance against oxidation
- Good detergency and dispersion
- Safe lubrication film at high temperatures
- Strong protection against wear, corrosion and foaming

Application **Veedol Multigrade Super 10W-40** is recommended for use in petrol and diesel engines, with or without turbo-charging, in passenger cars and delivery vans.

Performance Specifications API SL/CF
ACEA A3/B4-12
MB-Approval 229.1
Meets the requirements of
VW 502.00/505.00

Typicals Properties	Density at 15 °C, kg/l.....	0,873
	Viscosity -25 °C, mPa.s.....	6470
	Viscosity 40 °C, mm ² /s.....	95,40
	Viscosity 100 °C, mm ² /s.....	14,20
	Viscosity Index.....	153
	Flash Point COC, °C.....	224
	Pour Point, °C.....	-39
	Total Base Number, mgKOH/g.....	10,2
Sulphate Ash, %.....	1,29	

Veedol International B.V.

Kabelweg 21 | 1014 BA | Amsterdam | The Netherlands | Tel: +31(0)20-3584607 | Fax: +31(0)20-3313266

™ Registered trademark of Veedol International UK

The data mentioned in this product information sheet is meant to enable the reader to orient himself about the properties and possible applications of our products. Although this overview is composed with all possible carefulness on the stated date, the composer does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The reader is advised, specially for critical applications, to make the final product-choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.