The Professional's Choice in Motor Oil... For over a century

Revision date: 06.11.2015

VEEDOL SINTRON C1 5W-30

Description

Veedol Sintron C1 5W-30 is a fuel economy, universal motor oil, developed according to the most recent technology and based on specially selected synthetic base oils. By applying advanced additives the exceptional performance of this low SAPS motor oil is accentuated.

- · Lower fuel consumption
- Suitable for modern catalysts
- · Low combustion ash building (low SAPS)
- Fast cold start
- Safe lubrication film at high temperatures
- Very good detergency and dispersion
- Very strong protection against wear, corrosion and foaming

Application

Veedol Sintron C1 5W-30 is recommended for use in petrol and diesel engines, with or without turbo-charging, in passenger cars and delivery vans. Due to its special composition this product can be applied in vehicles with modern three way catalysts and diesel particle filters. Due to its low SAPS content this motor oil contributes to the extension of the lifetime of particle filters for diesel engines **Warning:** These oils have the lowest SAPS limits and may be unsuitable for use in some engines.

Performance Specifications

ACEA C1-12

Meets the requirements of: Ford WSS-M2C934-B

Jaguar Land Rover STJR.03.5005

Typicals Properties

Density at 15 °C, kg/l	0,849
Viscosity -30 °C, mPa.s	3900
Viscosity 40 °C, mm²/s	52,50
Viscosity 100 °C, mm²/s	9,46
Viscosity Index	166
Flash Point COC, °C	224
Pour Point, °C	39
Total Base Number, mgKOH/g	6,2
Sulphate Ash, %	0,49

Veedol International B.V.

Kabelweg 21 | 1014 BA | Amsterdam | The Netherlands | Tel: +31(0)20-3584607 | Fax: +31(0)20-3313266

[™] Registered trademark of Veedol International UK