



POWERTRON 5W-30

Synthetic Technology Premium Engine Oil

TECHNICAL DATA SHEET

Product Description

Veedol Powertron 5W-30 is a premium quality multigrade synthetic blend engine oil suitable for use in gasoline passenger car engines. Manufactured with hydro-treated synthetic base, polymers and advanced technology additives, it is specially formulated to provide exceptional performance in new generation vehicles.

Performance Specifications

Veedol Powertron 5W-30 meets or exceeds the performance requirements:

- API: SN
- ILSAC GF-5

It meets the requirements of most vehicle manufacturers

Features/Benefits

- Excellent performance during high & low temperature
- Improved fuel efficiency
- Ensured oil performance and reduced consumption
- High level of internal engine cleanliness
- Lower Emission.

Typical Properties

Test Parameters	ASTM Method	Typical Values
Kinematic Viscosity, @ 100°C, cSt	D 455	11.5
Cold Cranking Viscosity	D 5293	6600
Pour Point, °C		-42
Flash Point (COC), °C		>200

Properties mentioned above are typical only and minor variations which do not affect the product performances, are to be expected in normal manufacturing.

فيدول إنترناشيونال د.م.س.س

VEEDOL INTERNATIONAL DMCC

وحدة رقم 1501 | إنديغو آيكون | أرض رقم إف 3 | أبراج بحيرات الجميرا | دبي | الإمارات العربية المتحدة | تليفون: +971 4 3688 416 | فاكس: +971 4 3688 418

Unit No. 1501 | Indigo Icon | Plot No. F3 | Jumeirah Lakes Towers | P.O. Box No. 117019 | Dubai | United Arab Emirates

رقم الرخصة 32051 DMCC | رقم السجل التجاري 3002 DMCC

Tel: +971 4 3688 416 | Fax: +971 4 3688 418 | Email: enquiry@veedol.ae | www.veedol.ae

Licence No. DMCC-32051 | Registration No. DMCC3002

Company is registered & Licensed as a FREEZONE Company under the Rules & Regulations of DMCCA