

LUKOIL MOTO 2T

Two-stroke small engine oil

Approvals

- HUTER

Meet requirements

- ISO L-EGB
- JASO FB
- API TC

Product description

LUKOIL MOTO 2T – modern high-quality mineral multigrade oil, designed for 2-Stroke gasoline engines of motorcycles, mopeds, scooters and snowmobiles.

LUKOIL MOTO 2T has good detergent, antioxidant and anti-wear properties, which guarantee excellent engine performance under any conditions of operation and is formulated with high-quality base stocks and highly-effective advanced ash-less package of additives, which provides perfect protection of the engine even under the most severe conditions of operation, significantly decreases risk of sludge and deposits formation in outlet system, reduces the disruption of spark plugs and the risk of surface ignition, provides greater engine efficiency, decreases fuel consumption. Due to the careful formulation, LUKOIL MOTO 2T is virtually smokeless, and safe for the Environment.

Application

LUKOIL MOTO 2T is recommended for using in modern two-stroke engines of motorcycles, mopeds, scooters and snowmobiles. Proportion of the mixing must meet to the Operation and maintenance manual, but normally it is fuel:oil = 50:1

The product name in an order: Motor oil for two-stroke gasoline engines LUKOIL MOTO 2T, STO 79345251-002-2008

Typical test data

The information given in the typical data does not constitute a specification but is an indication based on current production and can be affected by allowable production tolerances. The right to make modifications is reserved by OOO "LLK-International"

Property	Test methods	Value
Density at 15 °C, kg/m ³	ASTM D1298 / ASTM D4052	894
Kinematic viscosity at 100 °C, mm ² /s	ASTM D445	14.5
Viscosity index	ASTM D2270	94
Total Base Number, mg KOH/1 g oil	ASTM D2896	1.4
Sulphated ash, %	ASTM D874	0.19
Flash Point, COC, °C	ASTM D92	242
Pour Point, °C	GOST 20287 B	-17