



Product Data

Visco Diesel 15W-40

Premium Diesel Engine Oil

Description

BP Visco Diesel 15W-40 is a premium quality versatile oil specifically designed to meet the demands of the high performance turbocharged diesel engines used in modern cars and light commercial vehicles.

It is also suitable for use in normally aspirated diesel engines and its advanced formulation makes it ideally suited to mixed fleet applications.

Application

Visco Diesel 15W-40 is suitable for use in automotive diesel engines where the manufacturer recommends an API CH-4 or earlier specification 15W-40 lubricant.

Advantages

BP Visco Diesel 15W-40 is a quality engine oil with the following benefits:

- Formulated for diesel engines.
- Excellent high temperature cleanliness and wear protection.
- Ideally suited to mixed diesel fleet applications.

Typical Characteristics

Name	Method	Units	Visco Diesel 15W-40
Density @ 15C	ASTM D4052	g/ml	0.884
Viscosity, Kinematic 100C	ASTM D445	mm ² /s	14.4
Viscosity, CCS -20C (15W)	ASTM D5293	mPa.s (cP)	6800
Viscosity, Kinematic 40C	ASTM D445	mm ² /s	106
Viscosity Index	ASTM D2270	None	140
Ash, Sulphated	ASTM D874	% wt	1.47
Flash Point PMCC	ASTM D93	°C	200
Pour Point	ASTM D97	°C	-24

Product Performance Claims

API CH-4/SJ

Storage

All packages should be stored under cover. Where outside storage is unavoidable drums should be laid horizontally to avoid the possible ingress of water and damage to drum markings. Products should not be stored above 60°C, exposed to hot sun or freezing conditions.

Visco Diesel 15W-40

27 May 2011

BP, Visco Diesel 15W-40 and the BP logo are trademarks of BP p.l.c., used under licence.

This data sheet and the information it contains is believed to be accurate as of the date of printing. However, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version of this data sheet. It is the responsibility of the user to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations. Material Safety Data Sheets are available for all our products and should be consulted for appropriate information regarding storage, safe handling, and disposal of the product. No responsibility is taken by either BP plc or its subsidiaries for any damage or injury resulting from abnormal use of the material, from any failure to adhere to recommendations, or from hazards inherent in the nature of the material. All products, services and information supplied are provided under our standard conditions of sale. You should consult our local representative if you require any further information.

10 Junction Avenue , Parktown , Johannesburg , 2193 , South Africa
+27 11 488 5111, 0860 222 166 (SA), 0800 111 551 (SA)
www.castrol.co.za